

TrueNet®

Category 5e Four-Pair Riser Cable



ADC's TrueNet® Category 5e riser cable is an integral part of the TrueNet channel solution. Thanks to AirES® technology this cable is up to 28% smaller than competitive products, and this reduction in size also results in a safer product with less material to burn in the unlikely event of a fire. AirES also improves attenuation, crosstalk, delay skew and impedance due to the unique dielectrical characteristics associated with air.

Features:

- Patented AirES technology
- Manufactured with lead-free materials
- Patented impedance matching for zero bit-errors
- Designed for Gigabit Ethernet applications
- Component of the TrueNet zero bit-error warranty
- Available in a side-by-side configuration

Compliances:

- UL Subject 444
- (UL)-C(UL) Type CMR/CMG
- (UL)-C(UL) Type CM/CMH
- ICEA S-90-661
- NEC 800 Type CMR or CM
- ISO/IEC 11801 Class D
- ETL verified TIA/EIA-568-B.2 Category 5e horizontal cable requirements

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891



TrueNet®

Category 5e Four-Pair Riser Cable

Specifications

CONSTRUCTION

Features AirES technology

Conductors:	24 AWG solid bare copper
Insulation:	Polyolefin
Pairing:	Short, staggered pair lays
Jacket:	Lead-free, flame retardant PVC
Nominal outer diameter:	4.7 mm (.185")

ELECTRICAL CHARACTERISTICS

Conductor DC resistance (maximum):	9.38 Ω /100 meters (28.6 Ω /1000 ft) @ 20 °C (68 °F)
DC resistance unbalance (maximum):	2%
Mutual capacitance (maximum):	5.6 nF/100 meters (17 pF/ft)
Operating temperature (maximum):	75 °C (167 °F)
Operating voltage (maximum):	300 VDC
Worst case cable skew:	25 nS/100 meters (25 nS/328 ft)
Nominal velocity of propagation:	69%

6 / 0 5 • 1 3 2 4 6 7 9 Category 5e Four-Pair Riser Cable



TrueNet®

Category 5e Four-Pair Riser Cable

6 / 0 5 • 1 3 2 4 6 7 9 Category 5e Four-Pair Riser Cable

FREQ (MHz)	FITTED IMPEDANCE (Ohms)	INSERTION LOSS (dB/100m)		RETURN LOSS (dB/100m)		Pair-Pair NEXT (dB/100m)		PSNEXT (dB/100m)	
	SPEC	Max	TIA Spec	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec
1	100 +/- 5	1.9	2.0	33.7	20.0	80.2	65.3	78.0	62.3
4	100 +/- 3	3.8	4.1	38.9	23.0	68.7	56.3	66.6	53.3
8	100 +/- 3	5.4	5.8	35.6	24.5	63.0	51.8	61.7	48.8
10	100 +/- 3	6.1	6.5	36.4	25.0	61.8	50.3	59.2	47.3
16	100 +/- 3	7.7	8.2	36.9	25.0	59.0	47.2	55.8	44.2
20	100 +/- 3	8.7	9.3	35.1	25.0	60.0	45.8	58.3	42.8
25	100 +/- 3	9.8	10.4	36.4	24.3	55.7	44.3	54.2	41.3
31.25	100 +/- 3	10.9	11.7	33.3	23.6	53.7	42.9	52.3	39.9
62.5	100 +/- 3	15.6	17.0	31.6	21.5	51.6	38.4	50.4	35.4
100	100 +/- 3	20.0	22.0	32.8	20.1	46.4	35.3	44.1	32.3
155	100 +/- 3	25.1		23.7		44.6		43.1	
200	100 +/- 3	28.8		24.8		46.6		43.3	
250	100 +/- 3	32.2		23.3		42.1		40.8	
300	100 +/- 3	35.5		21.9		42.0		39.1	
350	100 +/- 3	38.6		21.7		34.5		32.9	

FREQ (MHz)	Pair-Pair ACR (dB/100m)		PSACR (dB/100m)		Pair-Pair ELFEXT (dB/100m)		PSELFEXT (dB/100m)	
	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec
1	78.3	63.3	76.1	60.3	74.6	63.8	73.8	60.8
4	64.9	52.2	62.8	49.2	63.5	51.8	62.5	48.8
8	57.5	46.0	56.3	43.0	56.0	45.7	55.4	42.7
10	55.7	43.8	53.1	40.8	54.1	43.8	53.8	40.8
16	51.3	39.0	48.1	36.0	51.2	39.7	50.7	36.7
20	51.3	36.5	49.6	33.5	49.3	37.8	48.7	34.8
25	46.0	33.9	44.4	30.9	47.9	35.8	47.2	32.8
31.25	42.7	31.2	41.4	28.2	45.2	33.9	44.8	30.9
62.5	36.0	21.4	34.8	18.4	39.4	27.9	38.8	24.9
100	26.4	13.3	24.1	10.3	36.6	23.8	35.7	20.8
155	19.4		18.0		30.4		29.5	
200	17.8		14.5		28.0		28.0	
250	9.8		8.6		24.9		23.7	
300	6.6		3.7		24.7		24.8	
350					22.8		21.6	

NOTE: The above listed discrete frequency electrical performance values are provided for engineering information only. Actual compliance testing is based on swept frequency measurements. The spec values are based on TIA/EIA 568-B.2 specifications.

Ordering Information

Description	Weight (Lbs/kft)	Catalog Number*
4-pair cable, CMR flame rating		
Reel packaging	20	TN5ESR-XXYY
Reelx-1000'	20	TN5ESR-XXII
Reel in a box-1000'	22	TN5ESR-XXRB
4-pair cable, CM flame rating		
Reel packaging	20	TN5ESM-XXYY
Reelx-1000'	20	TN5ESM-XXII
Reel in a box-1000'	22	TN5ESM-XXRB

*To order cable sheath color, replace XX with:

BL = Blue
 WT = White
 GY = Gray
 GN = Green
 YL = Yellow
 RD = Red

*To designate reel length, replace YY with:

02 = 1000'
 04 = 2000'
 05 = 2500'
 06 = 3000'

SPEC SHEET

KRONE® is a registered trademark of ADC Telecommunications, Inc.



Web Site: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
 Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our web site.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
 Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

1324679 6/05 Original © 2005 ADC Telecommunications, Inc. All Rights Reserved