

KM8 RJ45 Modular Patch Panel II STP 24ports

Order No. 7022 1 055-24

Description	Weight/Pack	Pack
KM8 RJ45 Modular Patch Panel II STP 24ports (568 A/B)		1 piece



The modular patch panel is designed for setting up fully shielded 2-pair and 4-pair LAN cabling systems satisfying **Category 6** requirements in accordance with ISO/IEC 11801:2002, EN 50173-1:2002 and TIA/EIA 568-B

- Dimension: 19", 1U

The delivery comprises:

- Mounting frame (made of metal with black plastic panels) which has two labeling lines
- KM8 RJ45 jacks, fully shielded with LSA-PLUS simultaneous connection components
Cable management for defined wire guidance, spring clip for 360° shield contact
- Earth connection material
- 19" fixing material

KM8 RJ45 Modular Patch Panel II STP, 24Ports

Cable parameters:

- Conductor diameter range: 0.5 - 0.65 mm
- Wire diameter range, with insulation: 0.7 - 1.6 mm

Note on installation:

For installation of the modular patch panels, it is recommended that the mounting aid (Order number 6527 1 013-00) be used. For guidance of the patchcords, it is recommended that the cable manager 6527 1 006-01 be used.

Keyword for Index :
KM8 RJ45 Modular Patch Panel II STP

Copyright KRONE GmbH, Productmanagement, subject to change without notice !

Data from :

14-APR-2005 11:46:37