


TrueNet®

CopperTen® Four-Pair Riser Cable



An integral part of ADC's TrueNet® Structured Cabling System, CopperTen® is the world's first UTP structured cabling system to enable 10 Gigabit Ethernet over a full 100 meters. Installed in high-performance networks worldwide, the system's patent-pending design minimizes alien crosstalk and insertion loss and meets the performance requirements of IEEE 802.3an and TIA 568-B.2-10 draft standards.

Features:

- Patent-pending oblique elliptical offset filler minimizes alien crosstalk
- Manufactured with lead-free materials

Compliances:

- UL Subject 444
- (UL)-C(UL) Type CMR/CMG
- ICEA S-90-661
- NEC 800 Type CMR
- TIA/EIA 568-B.2-10 draft standard
- ISO/IEC 11801 Category 6A draft horizontal cable requirements

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891



TrueNet®

CopperTen® Four-Pair Riser Cable

Specifications

CONSTRUCTION CHARACTERISTICS

Conductor:	23 AWG solid bare copper
Insulation:	100% Polyolefin
Separator:	Flame retardant polyolefin
Jacket:	Non-lead, flame retardant PVC
Nominal Outer Diameter:	7.5 mm (.295") – 6.6 mm x 8.3 mm (.260" x .325")

MECHANICAL CHARACTERISTICS

Bend Radius	
During Installation:	8 x outer diameter
Installed:	4 x outer diameter
Pull Tension:	110 N (25#)

ELECTRICAL CHARACTERISTICS

Conductor DC Resistance @ 20 °C (68 °F) (Max):	9.38 Ω/100 m (28.6 Ω/1000 ft)
DC Resistance Unbalance (Max):	2%
Mutual Capacitance @ 20 °C (68 °F) (Max):	5.6 nF/100 m (17 pF/ft)
Operating Voltage (Max):	300 VDC
Worst Case Cable Skew:	40 ns/100 m (40 ns/ 328 ft)
Nominal Velocity of Propagation:	65%

ENVIRONMENTAL CHARACTERISTICS

Transport and Storage:	-20° to 75 °C (-4° to 167 °F)
Installation:	4° to 50 °C (39° to 122 °F)
Operation:	-20° to 75 °C (-4° to 167 °F)

7/07 • 104976AE CopperTen® Four-Pair Riser Cable



TrueNet[®] CopperTen[®] Four-Pair Riser Cable

7/07 • 104976AE CopperTen[®] Four-Pair Riser Cable

FREQ (MHz)	FITTED IMPEDANCE (Ohms)	INSERTION LOSS (dB/100m)		RETURN LOSS (dB/100m)		Pair-Pair NEXT (dB/100m)		PSNEXT (dB/100m)	
	SPEC	Max	TIA Spec	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec
1	100 ± 5	1.7	2.0	26.5	20.0	88.4	74.3	87.2	72.3
4	100 ± 3	3.4	3.7	31.1	23.0	82.8	65.3	80.0	63.3
8	100 ± 3	4.9	5.2	37.2	24.5	73.5	60.8	72.1	58.8
10	100 ± 3	5.5	5.9	30.3	25.0	73.9	59.3	71.7	57.3
16	100 ± 3	7.0	7.4	32.0	25.0	67.5	56.2	66.4	54.2
20	100 ± 3	7.8	8.3	35.2	25.0	70.0	54.8	68.5	52.8
25	100 ± 3	8.8	9.3	35.4	24.3	68.1	53.3	67.7	51.3
31.25	100 ± 3	9.9	10.4	38.9	23.6	67.4	51.9	64.7	49.9
62.5	100 ± 3	14.1	14.9	33.6	21.5	60.3	47.4	59.6	45.4
100	100 ± 3	18.0	19.0	28.1	20.1	59.2	44.3	57.8	42.3
155	100 ± 3	22.6	24.0	28.4	18.8	50.6	41.4	50.0	39.4
200	100 ± 3	25.8	27.5	27.3	18.0	52.5	39.8	51.4	37.8
250	100 ± 3	29.0	31.0	27.2	17.3	50.9	38.3	49.8	36.3
300	100 ± 3	31.8	34.2	25.0	16.8	46.9	37.1	46.4	35.1
350	100 ± 3	34.5	37.2	23.5	16.3	43.8	36.1	43.3	34.1
400	100 ± 3	37.0	40.0	24.5	15.9	47.2	35.3	44.7	33.3
450	100 ± 3	39.4	42.7	22.9	15.5	45.9	34.5	42.8	32.5
500	100 ± 3	41.6	45.3	21.3	15.2	48.2	33.8	47.0	31.8
550	100 ± 3	43.8		21.4		46.2		44.6	
600	100 ± 3	45.9		21.2		44.2		43.0	

FREQ (MHz)	Pair-Pair ACR (dB/100m)		PSACR (dB/100m)		Pair-Pair ELFEXT (dB/100m)		PSELFEXT (dB/100m)	
	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec	Min	TIA Spec
1	86.6	72.3	85.4	70.3	78.2	67.8	77.6	64.8
4	74.9	61.5	73.5	59.5	66.4	55.8	65.7	52.8
8	68.7	55.5	66.7	53.5	60.2	49.7	59.7	46.7
10	68.6	53.4	66.4	51.4	58.4	47.8	57.7	44.8
16	60.7	48.8	59.7	46.8	53.6	43.7	53.3	40.7
20	59.7	46.5	58.7	44.5	51.8	41.8	50.9	38.8
25	58.9	44.0	56.4	42.0	50.0	39.8	49.1	36.8
31.25	57.9	41.5	55.2	39.5	48.0	37.9	47.2	34.9
62.5	45.9	32.5	44.7	30.5	43.6	31.9	42.9	28.9
100	40.3	25.3	38.5	23.3	39.9	27.8	38.9	24.8
155	27.6	17.5	27.3	15.5	35.5	24.0	33.2	21.0
200	24.6	12.3	24.4	10.3	32.5	21.8	31.0	18.8
250	19.2	7.4	18.4	5.4	29.1	19.8	28.4	16.8
300	15.9	3.0	15.4	1.0	27.3	18.3	26.5	15.3
350	10.2	-1.0	9.7	-3.0	27.5	16.9	26.4	13.9
400	3.5	-4.7	2.8	-6.7	27.0	15.8	26.8	12.8
450	0.5	-8.2	0.0	-10.2	26.3	14.7	25.8	11.7
500	1.0	-11.4	-0.3	-13.4	23.4	13.8	22.7	10.8
550					23.6		22.9	
600					21.7		20.8	

NOTE: The above listed discrete frequency electrical performance values are provided for engineering information only. Actual compliance testing is based on swept frequency measurements. The spec values are based on TIA/EIA 568-B.2-10 specifications.

Ordering Information

Description	Catalog Number*
4-pair riser data cable 1000' reel	10G-A6TR-XX02

Additional packaging options are available, please contact ADC Technical Assistance Center.

*To order jacket color, replace XX with:

BL = Blue GN = Green
WT = White YL = Yellow
GY = Gray RD = Red

SPEC SHEET



Web Site: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our web site.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

104976AE 7/07 Revision © 2005, 2007 ADC Telecommunications, Inc. All Rights Reserved