

TrueNet®

CopperTen Augmented Category 6 F/UTP Patch Panels



ADC's F/UTP CopperTen patch panels can be used in data center, communications closet and workstation for 10G shielded performance. Installed in high-performance networks world wide, the system's design minimizes alien crosstalk and insertion loss and meets the performance requirements of IEEE 802.3an and TIA 568-B.2-10 draft standards.

Features:

- Mounts in standard EIA 19-inch (482.6mm) rack
- Designed specifically to be used with ADC Augmented Category 6 STP jack

SPEC SHEET



www.adc.com • +1-952-938-8080 • 1-800-366-3891

Specifications

Operating Temperature Range:
Safety Rating:
Flammability Rating:

-40° C to 70° C (-40° F to 158° F)
UL 1863
UL 94-V0

Ordering Information

Description	Catalog Number
CopperTen Augmented Category 6 F/UTP Patch Panels	
1U Patch Panel, Category 6 KM8 STP 24 ports	7022 1 155-24
1U Patch Panel, Category 6 KM8 STP 24 ports (unloaded)	7022 2 155-24

SPEC SHEET



Website: www.adc.com

From North America, Call Toll Free: 1-800-366-3891 • Outside of North America: +1-952-938-8080
Fax: +1-952-917-3237 • For a listing of ADC's global sales office locations, please refer to our website.

ADC Telecommunications, Inc., P.O. Box 1101, Minneapolis, Minnesota USA 55440-1101
Specifications published here are current as of the date of publication of this document. Because we are continuously improving our products, ADC reserves the right to change specifications without prior notice. At any time, you may verify product specifications by contacting our headquarters office in Minneapolis. ADC Telecommunications, Inc. views its patent portfolio as an important corporate asset and vigorously enforces its patents. Products or features contained herein may be covered by one or more U.S. or foreign patents. An Equal Opportunity Employer

104811AE 5/07 Original © 2007 ADC Telecommunications, Inc. All Rights Reserved