

The Xirrus XE-2000 is a ceiling-mounted enclosure for the Xirrus Wireless LAN Array and is designed for use in open office spaces.

The XE-2000 replaces a single 2' x 2' drop ceiling tile. The dome is mounted on a fully hinged locking door providing easy access to equipment and cables for authorized technicians only. The XE-2000 is UL Listed and may be used in a plenum ceiling. The XE-2000 requires 4" of space above the drop ceiling for installation. Attach the enclosure to building structure with 3/8" threaded rod from each corner support bracket. The enclosure includes a cable pass-through port with a fire-stop foam seal. Dual locks secure the door.



Specifications

Benefits:

- Makes installation in drop down ceilings a snap
- Secures the Xirrus WLAN Array from theft or damage
- Prevents damage from water and dust

Product Model Number: XE-2000

Product Description:

Enclosure, Indoor-Only, Ceiling Drop-in 2'x2', Lockable Door

Ordering Part Number:

XE-2000, in, 2x2

Materials

- Enclosure: .060" thick sheet aluminum
- Dome: opaque plastic, white
- Back plate: plastic

Packaging

- 1 Enclosure/Carton

Shipping Weight: 21lb

Approvals

- UL Listed

Specifications

- Enclosure: 23 3/4"W x 23 3/4"L x 3"D
- Dome : 3.1" High, 19"Diameter
- Product Weight: 10.5 lb
- Back plate accommodates Xirrus WLAN Array

Installation

- Customer must provide threaded rod and installation hardware

Cable Entry and Exit Specifications

- (1) 3" wide x 3/4" high edge-protected cable access port
- Includes approved fire-foamsealing kit